

1. (THREE TIMES AMENDED) A method of receiving an analog broadcasting signal and a digital broadcasting signal, comprising:

- selecting one of a digital broadcasting channel and an analog broadcasting channel;
- receiving the digital broadcasting signal if the digital broadcasting channel is selected and separating the digital broadcasting signal into an MPEG processed video signal and an MPEG processed audio signal using MPEG processing;
- receiving the analog broadcasting signal if the analog broadcasting channel is selected, extracting a synchronous signal from the received analog broadcasting signal, adjusting the extracted synchronous signal to a synchronous signal of the digital broadcasting signal, and separating the analog broadcasting signal into an analog broadcasting audio signal and an analog broadcasting video signal;
- selectively encoding one of the MPEG processed video signal separated from the digital broadcasting signal and predetermined additional information according to the extracted synchronous signal;
- selectively transmitting one of the additional information overlapped with the analog broadcasting video signal separated from the analog broadcasting signal and the additional information overlapped with the MPEG processed video signal separated from the digital broadcast signal in accordance with the encoding selected in the encoding of the MPEG processed video signal; and
- selectively transmitting one of the MPEG processed audio signal separated from the digital broadcasting signal and the analog broadcasting audio signal separated from the analog broadcasting signal.

5. (TWICE AMENDED) A digital broadcasting receiver which MPEG processes a digital video signal and a digital audio signal from a received carrier signal as an MPEG processed video signal and an MPEG processed audio signal and receives and transmits an analog broadcasting signal to a television receiver, comprising:

- a controller to determine whether an analog broadcasting channel or a digital broadcasting channel is selected, to generate a plurality of control signals having respectively different information, and to receive the analog or digital broadcasting signal according to the selection;

- a digital broadcasting tuner to receive the digital broadcasting channel according to the selection of the controller;

- an air tuner to receive the analog broadcasting signal according to the selection of the

controller;

a synchronous separation unit to extract a synchronous signal from the analog broadcasting signal received from said air tuner and to separate the analog broadcasting signal into an analog audio signal and an analog video signal;

an additional information process unit to generate additional information according to a first [one] control signal of the plurality of control signals from said controller;

a video encoder unit to encode the MPEG processed video signal and the additional information into an encoded analog video signal according to a second control signal of the plurality of control signals and the synchronous signal;

a video mix unit to mix the analog video signal from said air tuner and the encoded analog video signal, and to transmit the mixed signal;

a digital/analog converting unit to convert the MPEG processed audio signal to an MPEG processed analog audio signal; and

an audio selection unit to select and transmit the [converted] MPEG processed analog audio signal and the analog audio signal from said air tuner according to a third [one] control signal of the plurality of control signals.

6. (TWICE AMENDED) The digital broadcasting receiver of claim 5, further comprising:

a luminance/color separation unit to separate the mixed signal transmitted by the video mix unit into a luminance signal and a color signal, and transmit the separated mixed signal.

9. (TWICE AMENDED) The digital broadcasting receiver of claim 5, wherein said video mix unit includes a switcher which maps the additional information other than a transparency between the encoded MPEG processed video signal from said video encoder unit and the analog video signal from said air tuner, and outputs the mapped additional information.

10. (TWICE AMENDED) The digital broadcasting receiver of claim 7, wherein said video mix unit includes a switcher which maps the additional information other than a transparency between the encoded MPEG processed video signal from said video encoder unit and the analog video signal from said air tuner, and outputs the mapped additional information.

11. (ONCE AMENDED) A digital broadcast receiver receives an analog broadcasting signal and a digital broadcasting signal, comprising:

a controller to determine whether the analog broadcasting signal or the digital

a synchronous separation unit to separate the analog broadcasting signal into a synchronous signal, an analog video signal, and an analog audio signal;

a video encoder to encode a video signal from the digital broadcasting signal and the additional information according to the separated synchronous signal; and

a video mix unit to overlap the additional information with the analog video signal from the synchronous separation unit in response to the analog broadcasting signal being displayed, and to select the video signal from the digital broadcasting signal and the additional information in response to the digital broadcasting signal being displayed, to transmit an image signal.

18. (ONCE AMENDED) A broadcasting receiver which receives a digital broadcasting signal and an analog broadcasting signal, comprising:

a tuning unit to selectively receive the digital or analog broadcasting signal; and

a processing unit to process the digital or analog broadcasting signal in accordance with the selection by said tuning unit, and to synchronize phases of the digital and analog broadcasting signals upon the tuning unit changing selection between the digital or analog broadcasting signal.

20. (ONCE AMENDED) A broadcasting receiver for a display receiver and which receives a digital broadcasting signal and an analog broadcasting signal, comprising:

a tuning unit to selectively receive the digital or analog broadcasting signal;
a processing unit to process the digital or analog broadcasting signal in accordance with the selection by said tuning unit;

an additional information processing unit to generate additional information corresponding to the digital or analog broadcast signal selected; and

a video mix unit to selectively output the processed digital broadcasting signal with the additional information or the processed analog broadcasting signal with the additional information, wherein the additional information corresponding to the digital broadcasting signal and the analog broadcasting signal are the same.

REMARKS

INTRODUCTION:

In accordance with the foregoing, claims 1, 5, 6, 9-11, 18, and 20 no new matter is being